


# INBOARD ALARMS AND NONATONE

## KD Demihorn / KW Whistle



Description	KD Demihorn			KW Whistle		
Sound	—			—		
Use	General alarm· Fire alarm· Tell call ·CO2 alarm			General alarm		
Model	440	660	800	32×1500	32×2000	32×2400
frequency	440Hz	660Hz	800Hz	1500Hz	2000Hz	2400Hz
Sound level	130dB/1m(C)			125dB/1m(C)		
Consumption	5~8ℓ/s			10~13ℓ/s		
Air pressure	0.4~0.9MPa			0.6~0.9MPa		
Power source	AC 110/220V , DC 24V					
Current	22VA					
Overall length	375mm	238mm	181mm	314mm	273mm	243mm
Horn diam.	φ180mm	φ140mm	φ125mm	φ32mm	φ32mm	φ32mm
Non explosion area	○	○	○	○	○	○
Explosion area	Separate type ○	Separate type ○	Separate type ○	—		
Weight	Approx. 2.6 kg			Approx. 1.5 kg		
Code No.	3302	3303	3304	3311	3313	3312

Used in very noisy engine or pump rooms. many types of tones are available for telephone and emergency alarm.

- Alarm air horn is most effective of especially in the engine room and valve with adjustable loudness control mechanism provided.

- Available to supply the explosion proof type valve of d2G4 grade. (NK type approval)

- Separate type provided at explosion area, setting horn and non explosion area setting valve, they are located up to 3m from unit, service ability and audibility are well maintained.



## Nonatone W.T. Electric sounder MZLW

- Maximum sound : 105dB/1m
- Choosing the tone from 9 kinds.
- Pilot lamp is using high luminance LED, there is good visibility and long life time.



Description	MZLW-DC	MZLW-AC	
Voltage	DC24V	AC100V	AC220V
Current	270mA	70mA	30mA
Frequency	—	50/60Hz	
Operation voltage range	DC20~30V	Rated voltage ±10%	
Sound level	103dB/m((Up to 105))		
Protection degree	IP56		
Weight	Approx. 0.7kg	Approx. 0.9kg	
Ambient temperature	0~45Degree		
Material	Polycarbonate		
Color	Munsell 5R4/13, 7.5BG7/2		
Code No.	4151GDC	4151GAC100	4151GAC220

